

# STAR FERTILIZER SPREADER

Precision and high efficiency

MBC middle series

Low machine body for easy fertilizer loading

Polyethylene hopper for long durability and no rust



Removable hopper for easy maintenance

**MBC4561**  
(Spout, electric shutter opening )

**MBC6020**  
(2 spinner, manual shutter opening )

**1-Spinner type**



With 4 stainless steel spinner blade

**Spout Type**



Highly Durable plastic spout

**2-Spinner type**



Wide and powerful spreading with 2 disks

## SPECIFICATIONS (Approximate)

	Model			Hopper Capacity (litter)	Dimension (cm)			Weight (kg)	Performance		PTO (rpm)	Tractor, RequiredHp kW (PS)
	Manual shutter	Electric shutter	Hydraulic shutter		Length	Width	Height		Working speed (km/hr)	Spreading width (m)		
1 spinner	MBC4550	MBC4551	-	450	150	165	99	130	4 ~ 10	Granular 8 ~ 10m Sandy 4.5 ~ 6.5m	350 ~ 450	29.5 ~ 51.5kW (40 ~ 70PS)
	MBC6050	MBC6051	-	600		168	109	135				33 ~ 59kW (45 ~ 80PS)
	MBC8550	MBC8551	-	850		125	140	40.5 ~ 73.5kW (55 ~ 100PS)				
Spout	MBC4560	MBC4561	-	450	150	165	99	155	4 ~ 10	Granular 9 ~ 11m Sandy 5 ~ 7m	450 ~ 500	29.5 ~ 51.5kW (40 ~ 70PS)
	MBC6060	MBC6061	-	600		168	109	160				33 ~ 59kW (45 ~ 80PS)
	MBC8560	MBC8561	-	850		125	165	40.5 ~ 73.5kW (55 ~ 100PS)				
2 Spinner	MBC4520	-	MBC4522	450	150	165	99	180	4 ~ 10	Granular 20 ~ 24m Sandy 8 ~ 12m	450 ~ 500	29.5 ~ 51.5kW (40 ~ 70PS)
	MBC6020	-	MBC6022	600		168	109	185				33 ~ 59kW (45 ~ 80PS)
	MBC8520	-	MBC8522	850		125	190	40.5 ~ 73.5kW (55 ~ 100PS)				

Remarks : Length and height do not include shutter lever.

Figures, technical data, dimensions and weights are subject to change without notice.

## IHI STAR Machinery Corporation

1061-2 Kamiosatsu, Chitose-shi, HOKKAIDO 066-8555 JAPAN

TEL +81-123-26-2210 FAX +81-123-26-2412

E-mail [star@star-web.jp](mailto:star@star-web.jp)

Website <http://www.ihistar.com/english/>

2008.04