



ROTARY HAY MAKER

Multiple operation Tedding / Raking


TGR2220/2630



MGR2630



MGR2220



Raking / Tedding / Spreading / Transporting are possible by shifting the change lever.



Wheel height can be adjusted easily with pin insertion. Set to field condition or kind of work.

Features of MGR2630 only



The machine follows a tractor track flexibly with auto-swivel hitch, and the raking quality is uniform even around corners.



Easily detachable tine arms are stored at front frame. At transport, width is 135cm

SPECIFICATIONS (Approximate)

Model	Working width (cm)		Dimensions (cm)			Weight (kg)	Number of arm	Working speed (km/hr)		Working capacity (Ton/hr)		Tractor, Required Hp
	Tedding	Raking	Length	Width	Height			Tedding	Raking	Tedding	Raking	
MGR2220	150	220	195	220 (170)	95	125	4	5 ~ 8	4 ~ 8	55 ~ 85	70 ~ 130	11 ~ 26kW (15 ~ 35PS)
MGR2630	175	260	220	260 (135)	105	155	6			65 ~ 100	80 ~ 155	13 ~ 29.5kW (18 ~ 40PS)

Remarks : Working capacity subject to change depending on the type and/or moisture content of material.

Figures, technical data, dimensions and weights are subject to change without notice.

IHI STAR Machinery Corporation

1061-2 Kamiosatsu, Chitose-shi, HOKKAIDO 066-8555 JAPAN

TEL +81-123-26-2210 FAX +81-123-26-2412

E-mail star@star-web.jp

Website <http://www.ih-star.com/english/>

2008.04