



# FORAGE CUTTER & MOUNTED CUTTER

Driven by electric motor or engine SFC/1440·1840·2340

Driven by a tractor PTO MFC/1840·2340

Compactly designed SFC/MFC series for chopping forage, hay, straw, corn, corn stalk, squeezed sugar cane, palm leaf and beet tops.

Highly durable stainless steel chute ensures the long life of the machine.

Tough & High-performance feed roller



Easy maintenance with detachable casing



SFC1440



SFC1840



MFC2340

Sharp cutting / powerful blower flywheel



Visible tachometer (for MFC series)



Wide feeding conveyor (for 1840,2340)



ACS1400 corn shredder (for SFC1440)



ASW3000 support wheel (for MFC)



## SPECIFICATIONS (Approximate)

Model	Dimensions(cm)			Weight (kg)	Rotary knives	Width of feed roller(cm)	Capacity (kg/hr)	Cutting length	Power,required	
	Length	Width	Height						Motor (kW)	Engine (PS)
SFC1440	105	93	142	70	2	14	900 ~ 3200	13,23 37,60	0.4 ~ 2.9	0.5 ~ 4.0
SFC1840	180	125	175	160		18	900 ~ 5000	10,20 45,60	1.8 ~ 5.1	2.5 ~ 7.0
SFC2340	245	130	180	210		23	1200 ~ 6600		2.9 ~ 7.5	4.0 ~ 10.0
Model	Dimensions(cm)			Weight (kg)	Rotary knives	Width of feed roller(cm)	Capacity (kg/hr)	Cutting length	Required Tractor HP	
	Length	Width	Height						kW	PS
MFC1840	200	125	235	250	2	18	900 ~ 5000	10,20 45,60	11 ~ 18	15 ~ 25
MFC2340	270	130	240	310		23	1200 ~ 6600		15 ~ 22	20 ~ 30

Remarks : Working capacity subject to change depending on the type and/or moisture content of material.  
Working capacity and cutting length subject to theoretical value.  
Figures, technical data, dimensions and weights are subject to change without notice.

### Optional parts

CORN SHREDDER ATTACHEMENT (ACS1400) for good silage  
CASTER (ACW1400) for easy movement  
MOTOR BASE (AMD1400/2300) for applying motor operation

## IHI STAR Machinery Corporation

1061-2 Kamiosatsu, Chitose-shi, HOKKAIDO 066-8555 JAPAN

TEL +81-123-26-2210 FAX +81-123-26-2412

E-mail [star@star-web.jp](mailto:star@star-web.jp)

Website <http://www.ihi-star.com/english/>