



ROUND BALER

With variable chamber TVR2300WNT

From 60cm, to 100cm.




Simple switch box

Bale diameter can be set to 10 different levels with the switch box



Net binding / Twine binding



Binding system can easily be set to between **NET/TWINE** according to the operation.

2P swivel hitch connection



With 2P swivel hitch traction, high mobility can be expected even in corner operation.

Speedy baling with rubber belts



5 rubber belts enable baling with high density (for silage and dried hay) or low density (for wet hay).

Standard cutting device



8 cutting knives cut material in pieces, the bale can be broken up easily for feeding even high density.

SPECIFICATIONS (Approximate)

Model	Bale size (cm) Diameter × width	Dimensions (cm)			Weight (kg)	Width of pick up (cm)	Cutting device	Working speed (km/hr)	Tire size	Tractor, Required Hp
		Length	Width	Height						
TVR2300WNT	D(60 ~ 115) × W 100	340	205	230	1670	4 ~ 10	8 knives	4 ~ 8	12.5L-15 -8PR	37 ~ 59kW (50 ~ 80PS)

Others : • Binding method • • Twine / Net • 2P swivel hitch connection
• 1 double action hydraulic output is needed. • Automatic roller chain lubrication

Remarks : Working capacity subject to change depending on the type and/or moisture content of material.
Bale size and Bale weight varies depending on materials.
Figures, technical data, dimensions and weight are subject to changing without notice.

IHI STAR Machinery Corporation

1061-2 Kamiosatsu, Chitose-shi, HOKKAIDO 066-8555 JAPAN
 TEL +81-123-26-2210 FAX +81-123-26-2412
 E-mail star@star-web.jp
 Website <http://www.ih-star.com/english/>